



# SON KING Enterprises Co., Ltd.

No 14, Lane 359, Hsiao-Chien Rd., YangMei, TaoYuan, Taiwan

TEL: 886-3-4881801

FAX:886-3-4755249

## Ozone generator SKO3-230500

### Character

| Items                   | Contents  |
|-------------------------|---|
| 1. Description          | Ozone Generator   |
| 2. Model                | SKO3-230500   |
| 3. Input Voltage        | 220VAC ~ 240VAC   |
| 4. Input Frequency      | 50Hz/60Hz   |
| 5. Input Current        | Less than 100mA (at 230VAC)   |
| 6. Output Voltage       | 28KVAC PK $\pm$ 15%   |
| 7. Output Concentration | 500mg/m <sup>3</sup> (Base on our ozone measurement ANSEROS OZOMAT MP-6060)   |
| 8. Output Frequency     | 15KHz   |
| 9. Materials            | <p>(1) The black case is made by ABS.</p> <p>(2) High voltage transformer is sealed up in epoxy to prevent humidity. (Epoxy is burn-proofing.)</p> <p>(3) There are 2 input wires for 20# AWG (1015 20AWG VW-1 105 600V), one is brown and the other is black. They are made by burn-proofing material UL rating. The length is approx. 730mm.</p> <p>(4) There is a fuse connected in brown input wire. The rating is 0.5Amp. Both ends of the fuse could withstand the pull of 3.5Kg.</p> <p>(5) There are 2 output silicone wires, one is red and the other is black. They are made by burn-proofing material. The length is 150mm. There is a ring tongue terminal at one end of the input wires. They connect to the ozone tube.</p> |